Drawings

Models DY015, DY025, DY040, DY050, DY080 and DY100 (digitalYEWFLO)
High Process Temperature Version(/HT) and Cryogenic Version(/LT)
Digital Vortex Flowmeter (Remote and Flange type)

Unit: mm
(approx. inch)



TYPE		INTEGRAL/REMOTE																					
CODE		DY015 (15mm,½in) Only for /LT										DY025 (25mm,2in) /LT, /HT											
PROCESS CONNECTION		BJ1	BJ2	BJ4	BA1 BS1	BA2 BS2	BA4 BS4	BA5 BS5	BD1 - BD4	BD5 - BD6	CA4	CA5	BJ1	BJ2	BJ4	BA1 BS1	BA2 BS2	BA4 BS4	BA5 BS5	BD1 BD4	BD5 BD6	CA4	CA5
L		130 (5.12)						160 (6.30)	130 (5.12)		140 (5.51)	160 (6.30)	150 (5.91)						190 (7.48)	150 (5.91)		170 (6.69)	190 (7.48)
C		14.6 (0.57)											25.7 (1.01)										
D		95 (3.74)	95 (3.74)	115 (4.53)	88.9 (3.50)	95.3 (3.75)	95.3 (3.75)	120.7 (4.75)	95 (3.74)	105 (4.13)	95.3 (3.75)	120.7 (4.75)	125 (4.92)	125 (4.92)	130 (5.12)	108 (4.25)	124 (4.88)	124 (4.88)	149.4 (5.88)	115 (4.53)	140 (5.51)	124 (4.88)	149.4 (5.88)
H		421 (16.57)	421 (16.57)	431 (16.97)	418 (16.46)	421 (16.57)	421 (16.57)	434 (17.09)	421 (16.57)	426 (16.77)	421 (16.57)	434 (17.09)	438 (17.24)	438 (17.24)	441 (17.36)	430 (16.93)	438 (17.24)	438 (17.24)	450 (17.72)	433 (17.05)	446 (17.56)	438 (17.24)	450 (17.18)
H1		270 (10.63)											272 (10.71)										
T		12 (0.47)	14 (0.55)	20 (0.79)	11.2 (0.44)	14.2 (0.56)	21 (0.83)	28.8 (1.13)	16 (0.63)	20 (0.79)	19.9 (0.78)	28.8 (1.13)	14 (0.55)	16 (0.63)	22 (0.87)	14.2 (0.56)	17.5 (0.69)	24 (0.94)	34.9 (1.37)	18 (0.71)	24 (0.94)	24 (0.94)	34.9 (1.37)
J		70 (2.76)	70 (2.76)	80 (3.15)	60.5 (2.38)	66.5 (2.62)	66.5 (2.62)	82.6 (2.25)	65 (2.56)	75 (2.95)	66.5 (2.62)	82.6 (2.25)	90 (3.54)	90 (3.54)	95 (3.74)	79.2 (3.12)	89 (3.50)	89 (3.50)	101.6 (4.00)	85 (3.35)	100 (3.94)	89 (3.50)	101.6 (4.00)
N		4 (0.16)											4 (0.16)										
G		15 (0.59)	15 (0.59)	19 (0.75)	15.7 (0.62)	15.7 (0.62)	15.7 (0.62)	22.4 (0.88)	14 (0.55)	14 (0.55)	15.7 (0.62)	22.4 (0.88)	19 (0.75)	19 (0.75)	19 (0.75)	15.7 (0.62)	19 (0.75)	19 (0.75)	25.4 (1.00)	14 (0.55)	18 (0.71)	19 (0.75)	25.4 (1.00)
WEIGHT	kg	4.6	4.7	6.3	4.5	4.7	5.0	7.1	4.6	5.8	4.9	7.2	7.3	7.5	9.0	7.0	7.6	8.1	11.5	7.3	10.0	8.3	11.8
	lb	10.14	10.36	13.89	9.92	10.36	11.03	15.66	10.14	12.79	10.80	15.88	16.10	16.54	19.85	15.44	16.76	17.86	25.36	16.10	22.05	18.30	26.02

TYPE		INTEGRAL/REMOTE																					
CODE		DY040 (40mm,1½in) /LT, /HT											DY050 (50mm,2in) /LT, /HT										
PROCESS CONNECTION		BJ1	BJ2	BJ4	BA1 BS1	BA2 BS2	BA4 BS4	BA5 BS5	BD1 - BD4	BD5 - BD6	CA4	CA5	BJ1	BJ2	BJ4	BA1 BS1	BA2 BS2	BA4 BS4	BA5 BS5	BD1 BD4	BD5	BD6	CA4	CA5
L		150 (5.91)						200 (7.87)	150 (5.91)		185 (7.28)	200 (7.87)	170 (6.69)						230 (9.06)	170 (6.69)			205 (8.07)	230 (9.06)
C		39.7 (1.56)											51.1 (2.01)											
D		140 (5.51)	140 (5.51)	160 (6.30)	127 (5.00)	155.4 (6.12)	155.4 (6.12)	177.8 (7.00)	150 (5.91)	170 (6.69)	155.4 (6.12)	177.8 (7.00)	155 (6.10)	155 (6.10)	165 (6.50)	152.4 (6.00)	165.1 (6.50)	165.1 (6.50)	215.9 (8.50)	165 (6.50)	180 (7.09)	195 (7.68)	165.1 (6.50)	215.9 (8.50)
H		453 (17.83)	453 (17.83)	463 (18.23)	446 (17.56)	460 (18.11)	460 (18.11)	472 (18.58)	458 (18.03)	468 (18.43)	460 (18.11)	472 (18.58)	482 (18.98)	482 (18.98)	487 (19.17)	481 (18.94)	487 (19.17)	487 (19.17)	513 (20.20)	487 (19.17)	495 (19.49)	502 (19.76)	487 (19.17)	513 (20.20)
H1		279 (10.98)											301 (11.85)											
T		16 (0.63)	18 (0.71)	26 (1.02)	17.5 (0.69)	20.6 (0.81)	28.8 (1.13)	38.2 (1.50)	18 (0.71)	26 (1.02)	28.8 (1.13)	38.2 (1.50)	16 (0.63)	18 (0.71)	26 (1.02)	19.1 (0.75)	22.4 (0.88)	31.8 (1.25)	44.5 (1.75)	20 (0.79)	26 (1.02)	28 (1.10)	33.3 (1.31)	46 (1.81)
J		105 (4.13)	105 (4.13)	120 (4.72)	98.6 (3.88)	114.3 (4.50)	114.3 (4.50)	124 (4.88)	110 (4.33)	125 (4.92)	114.3 (4.50)	124 (4.88)	120 (4.72)	120 (4.72)	130 (5.12)	120.7 (4.75)	127 (5.00)	127 (5.00)	165.1 (6.50)	125 (4.92)	135 (5.31)	145 (5.71)	127 (5.00)	165.1 (6.50)
N		4 (0.16)											4 (0.16)	8 (0.31)	8 (0.31)	4 (0.16)	8 (0.31)	8 (0.31)	8 (0.31)	4 (0.16)	4 (0.16)	4 (0.16)	8 (0.31)	8 (0.31)
G		19 (0.75)	19 (0.75)	23 (0.91)	15.7 (0.62)	22.4 (0.88)	22.4 (0.88)	28.4 (1.12)	18 (0.71)	22 (0.87)	22.4 (0.88)	28.4 (1.12)	19 (0.75)	19 (0.75)	19 (0.75)	19 (0.75)	19 (0.75)	19 (0.75)	25.4 (1.00)	18 (0.71)	22 (0.87)	26 (1.02)	19 (0.75)	25.4 (1.00)
WEIGHT	kg	8.6	8.8	12.3	8.5	9.7	11.7	16.6	9.2	13.1	12.1	16.7	11.5	12.0	14.7	12.1	13.6	15.2	26.9	11.7	14.7	15.6	16.2	27.3
	lb	18.96	19.40	27.12	18.74	21.39	25.80	36.60	20.29	28.89	26.68	36.82	25.36	26.46	32.42	26.68	29.99	33.52	59.32	25.80	32.41	34.40	35.72	60.20

TYPE		INTEGRAL/REMOTE																								
CODE		DY080 (80mm,3in) /LT, /HT											DY100 (100mm,4in) /LT, /HT												
PROCESS CONNECTION		BJ1	BJ2	BJ4	BA1 BS1	BA2 BS2	BA4 BS4	BA5 BS5	BD1 - BD2	BD3 - BD4	BD5	BD6	CA4	CA5	BJ1	BJ2	BJ4	BA1 BS1	BA2 BS2	BA4 BS4	BA5 BS5	BD1 - BD2	BD3 - BD4	BD5	BD6	CA4	CA5
L		200 (7.87)						245 (9.65)	200 (7.87)				235 (9.25)	250 (9.84)	220 (8.66)					240 (9.45)	280 (11.02)	220 (8.66)				270 (10.63)	285 (11.22)
C		71 (2.80)													93.8 (3.69)											
D		185 (7.28)	200 (7.87)	210 (8.27)	190.5 (7.50)	209.6 (8.25)	209.6 (8.25)	241.3 (9.50)	200 (7.87)	200 (7.87)	215 (8.46)	230 (9.06)	209.6 (8.25)	241.3 (9.50)	210 (8.27)	225 (8.86)	250 (9.84)	228.6 (9.00)	254 (10.00)	273 (10.75)	292.1 (11.50)	220 (8.66)	235 (9.25)	250 (9.84)	265 (10.43)	273 (10.75)	292.1 (11.50)
H		514 (20.24)	522 (20.55)	527 (20.75)	517 (20.35)	527 (20.75)	527 (20.75)	542 (21.34)	522 (20.55)	522 (20.55)	529 (20.83)	837 (21.14)	527 (20.75)	542 (21.34)	542 (21.34)	549 (21.61)	562 (22.13)	552 (21.73)	564 (22.20)	573 (22.56)	583 (22.95)	547 (21.54)	554 (21.81)	562 (22.13)	569 (22.40)	573 (22.56)	583 (22.95)
H1		318 (12.52)											333 (13.11)													
T		18 (0.71)	22 (0.87)	32 (1.26)	23.9 (0.94)	28.4 (1.12)	38.2 (1.50)	44.5 (1.75)	20 (0.79)	24 (0.94)	28 (1.10)	32 (1.26)	39.7 (1.56)	46 (1.81)	18 (0.71)	24 (0.94)	36 (1.42)	23.9 (0.94)	31.8 (1.25)	44.5 (1.75)	50.9 (2.00)	20 (0.79)	24 (0.94)	30 (1.18)	36 (1.42)	46 (1.81)	52.4 (2.06)
J		150 (5.91)	160 (6.30)	170 (6.69)	152.4 (6.00)	168.2 (6.62)	168 (6.61)	190.5 (7.50)	160 (6.30)	160 (6.30)	170 (6.69)	180 (7.09)	170 (6.69)	180 (7.09)	175 (6.89)	185 (7.28)	205 (8.07)	190.5 (7.50)	200.2 (7.88)	216 (8.50)	235 (9.25)	180 (7.09)	190 (7.48)	200 (7.87)	210 (8.27)	216 (8.50)	235 (9.25)
N		8 (0.31)	8 (0.31)	8 (0.31)	4 (0.16)	8 (0.31)	8 (0.31)	8 (0.31)	8 (0.31)	8 (0.31)	8 (0.31)	8 (0.31)	8 (0.31)	8 (0.31)	8 (0.31)												
G		19 (0.75)	23 (0.91)	23 (0.91)	19 (0.75)	22.4 (0.88)	22.4 (0.88)	25.4 (1.00)	18 (0.71)	18 (0.71)	22 (0.87)	26 (1.02)	22.4 (0.88)	25.4 (1.00)	19 (0.75)	23 (0.91)	25 (0.98)	19 (0.75)	22.4 (0.88)	25.4 (1.00)	31.8 (1.25)	18 (0.71)	22 (0.87)	26 (1.02)	30 (1.18)	25.4 (1.00)	31.8 (1.25)
WEIGHT	kg	17.8	20.4	25.8	20.4	24.2	25.8	36.1	19.8	20.4	24.5	27.4	27.5	36.7	23.2	27.2	38.5	27.7	36.3	51.2	56.3	23.6	27.8	33.4	40.1	53.2	57.0
	lb	39.25	44.98	56.89	44.98	53.36	56.89	79.60	43.66	44.98	54.02	60.42	60.64	80.92	51.16	59.98	84.89	61.30	80.04	112.90	124.14	52.04	61.30	73.65	88.42	117.31	125.69

(Note 1) The flow direction is opposite (right to left when facing onto indicator) in case of code / CRC.



Terminal Wiring

Remote Type Detector	A B	] Signal Output Terminal
	⏚	Ground Terminal

* Use DYC signal cable

All Rights Reserved, Copyright © 2000, Yokogawa Electric Corporation.
Subject to change without notice. Printed in Japan.

SD 01F06A00-05E
1st Edition: Dec. 22, 2000
5th Edition: Aug. 1, 2004