


AXR080 G □ 1 A □ 1 □  
AXR100 C □ 1 A □ 1 □


B J 1  
 B J 2  
 B G 1 1  
 B A 1  
 B A 2  
 B D 2

Process Connection	BJ1 (JIS10K)		BJ2 (JIS20K)		BG1 (JIS F12)		BA1 (ANSI Class 150)		BA2 (ANSI Class 300)		BD2(DIN PN16)		
Size code	080	100	080	100	080	100	080	100	080	100	080	100	
Size	80 (3)	100 (4)	80 (3)	100 (4)	80 (3)	100 (4)	80 (3)	100 (4)	80 (3)	100 (4)	80 (3)	100 (4)	
Lining code	A	A	A	A	A	A	A	A	A	A	A	A	
Face-to-face length	L <sup>0*2</sup> 200 (7.87)	250 (9.84)	200 (7.87)	250 (9.84)	200 (7.87)	250 (9.84)	200 (7.87)	250 (9.84)	200 (7.87)	250 (9.84)	200 (7.87)	250 (9.84)	
Outside dia.	øD 185 (7.28)	210 (8.27)	200 (7.87)	225 (8.86)	211 (8.31)	238 (9.37)	190.5 (7.50)	228.6 (9.00)	209.6 (8.25)	254.0 (10.00)	200 (7.87)	220 (8.66)	
Thickness	t <sup>*2</sup> 22 (0.87)	22 (0.87)	26 (1.02)	28 (1.10)	22 (0.87)	22 (0.87)	27.9 (1.10)	27.9 (1.10)	32.4 (1.28)	35.8 (1.41)	24 (0.94)	24 (0.94)	
Inter diameter of Grounding ring	ød 77 (3.03)	102 (4.02)	77 (3.03)	102 (4.02)	77 (3.03)	102 (4.02)	77 (3.03)	102 (4.02)	77 (3.03)	102 (4.02)	77 (3.03)	102 (4.02)	
Pitch circle dia.	øC 150 (5.91)	175 (6.89)	160 (6.30)	185 (7.28)	168 (6.61)	195 (7.68)	152.4 (6.00)	190.5 (7.50)	168.1 (6.62)	200.2 (7.88)	160 (6.30)	180 (7.09)	
Bolt hole interval	ø°	22.5	22.5	22.5	45	45	45	22.5	22.5	22.5	22.5	22.5	
Hole dia.	øh 19 (0.75)	19 (0.75)	23 (0.91)	23 (0.91)	19 (0.75)	19 (0.75)	19.1 (0.75)	19.1 (0.75)	22.4 (0.88)	22.4 (0.88)	18 (0.71)	18 (0.71)	
Number of holes	N	8	8	8	4	4	4	8	8	8	8	8	
Height	H1	187 (7.36)	211 (8.30)	195 (7.68)	218 (8.59)	200 (7.87)	225 (8.85)	190 (7.48)	220 (8.66)	200 (7.87)	233 (9.16)	195 (7.68)	216 (8.49)
Height	H2	95 (3.74)	106 (4.16)	95 (3.74)	106 (4.16)	95 (3.74)	106 (4.16)	95 (3.74)	106 (4.16)	95 (3.74)	106 (4.16)	95 (3.74)	106 (4.16)
Max. Height	Hi	349 (13.74)	372 (14.65)	357 (14.06)	380 (14.95)	362 (14.25)	386 (15.21)	352 (13.86)	362 (14.25)	394 (15.52)	357 (14.06)	377 (14.85)	
Weight kg (lb)		11.3 (24.9)	15.2 (33.5)	14.1 (31.0)	19.7 (43.4)	13.9 (30.6)	18.3 (40.3)	14.6 (32.2)	20.5 (45.2)	18.3 (40.3)	29.6 (65.2)	13.6 (29.9)	17.3 (38.1)

### Terminal configuration



\* When option code RA, RB, or RC is selected, the direction of electrical connection change as below.



### Terminal wiring

Terminal Symbols	Description
	Functional grounding
SUPPLY+ -	Power supply and current output
DO+ -	Digital output (One output can be selected from pulse, alarm or status outputs.)

\*1: When indicator code N is selected, subtract 5 mm (0.2 inch) from the value in the figure.  
\*2: Depending on the selection of grounding ring code and optional code, add the following value to "L" (face-to-face length) and "t" (thickness of flange).

	L	t	L	t	L	t
<b>Grounding Ring Code</b>	S, L, H		P, T		N	
Optional Code	None	+0	+0	+26 (1.02)	+13 (0.51)	-2 (0.08)
	GA, GC, GD (Special Gaskets)	+8 (0.31)	+4 (0.16)	+30 (1.18)	+15 (0.59)	-

Unless otherwise specified, difference in the dimensions are specified as : General tolerance = ± (Criteria of tolerance class IT18 in JIS B0401) / 2