

Specifications

Standard Specifications

General Specifications

- External Dimensions; Weight (with I/O module installed)
DR231: approximately 438 (W)×291 (H)×336 (D) mm; approximately 13 kg
DR232: approximately 438 (W)×291 (H)×301 (D) mm; approximately 9 kg
DS400: approximately 336 (W)×165 (H)×100 (D) mm; approximately 2.5 kg
DS600: approximately 422 (W)×176 (H)×100 (D) mm; approximately 3.5 kg
For model DR231, the DC power supply option adds 45 mm to the depth and 1.5 kg(f) to the weight.
- AC Power Supply
Rated supply voltage: 100 to 240 VAC
Usable supply voltage: 90 to 250 VAC
Rated supply frequency: 50/60 Hz
- DC Power Supply (/P6 option, only for the DR231 stand-alone model)
Rated supply voltage: 12 to 28 VDC
Usable supply voltage: 10 to 32 VDC
Terminal: Dedicated connector
Note: When both AC and DC power are connected to a DC power supply model, which of the power supplies is used depends on the voltage of the DC power supply connected as follows.

DC Power Supply Voltage	Power Supply Used
<20 V	AC power supply
20 to 28 V	Indeterminate
28 to 32 V	DC power supply

- Insulation Resistance
At least 20 MΩ at 500 VDC between the power supply and ground, between each terminal and the ground, and between input terminals
- Withstanding Voltage
Between power supply terminal and ground: 1,500 VAC (50/60 Hz, 1 min.)
Between input/output terminal and ground: 1,500 VAC (50/60 Hz, 1 min.)
- Normal Operating Conditions
Supply frequency: 50 Hz ±2% or 60 Hz ±2%
Ambient temperature: DR231, DR232 0 to 50°C (FD operation 5 to 40°C)
DS400, DS600 Panel mount -10 to 60°C
Desk-top -10 to 50°C
Ambient humidity: 20 to 80% RH (between -10 and 40°C)
- Safety Standards
CSA C22.2 No. 1010.1-92, IEC1010-1:1995, EN61010
- EMI Standard
EN55011:1991 Group 1 class A
- EMC Standard
EN50082-2:1995

System Configuration

- Configuration Method
DR231: Configure a system with this model by specifying necessary options, such as the input and communications functions, according to the model code when ordering.
- DR232: Configure a system with this model by combining one or more of the modules and subunits listed below.

Connecting Modules and Subunits (DR232)

- Standard Modules and Software for System Configuration
The following modules and software can be installed in a main unit and subunit to configure a data acquisition system.
- Input Modules: Universal (DCV, TC, RTD and DI), DCV/TC/DI dedicated, power monitor, strain, pulse, direct current (mA) and digital input
Connectable to DS400 and DS600
- Communications Modules: Ethernet, GP-IB, RS-232C and RS-422A/485
Connectable to DR232 main unit
- Alarm Contact Output Modules: 4 contacts (C contact: NO-C-NC) and 10 contacts (A contact: NO-C)
Connectable to DR232 Main unit or DS400 and DS600
- DI/DO Modules: Two alarm output contacts (NO-C-NC) and fail output
Connectable to DR232 Main unit or DS400 and DS600
Up to 1 module/1 system can be connected.
- Extension Modules: Interfaces for remote power supply
One extension module can be connected to each DS400 and DS600.
(should be used with extension base units)
- Software: DAQ 32(standard software)
DAQ 32 Plus (optional software)
- Types and Number of Modules That Can Be Connected
DR231: Specify the types of modules and the number according to the model code.
DR232: Communications module, DI/DO module or alarm contact output module
DS400/600: Input module, alarm contact output modules, DI/DO module and extension modules.
Four or six modules can be connected.

- Connection of Subunits
DR231: Cannot be connected.
DR232: Up to 6 subunits can be connected. One subunit can be installed on the rear panel by screws.

Input Section

- Number of Input Channels
DR231: 10 to 30 channels (Specify the number of channels when ordering.)
Power monitor input option: 2 or 6 channels
DR232: 0 channel. Expandable up to 300 channels by connecting subunits.
- Types of Input Modules
DR231: Universal (DC voltage, thermocouple, RTD and contact), DCV/TC/DI dedicated (specify the types when ordering), power monitor option
DR232: Universal (DC voltage, thermocouple, RTD and contact), DCV/TC/DI dedicated, power monitor, strain, pulse, direct current (mA) and digital input module
- Measurement Range: See the specifications for each input module.

- Measurement Interval: 0.5, 1, 2, 3, 4, 5, 6, 10, 12, 15, 20, 30 and 60 seconds
DR231: Maximum of 2 s per 30 channels
DR232: Maximum of 500 ms per 300 channels (including the subunit)
The measurement interval is dependent on the slowest input module if input modules of different measurement intervals are connected at the same time.
- A/D Integration Period
Manual selection or automatic switchover between 20 ms (50 Hz), 16.7 ms (60 Hz) and 100 ms (10 Hz)
Minimum measurement interval when the 100-ms integration mode becomes:
DR231: 30 channels: 6 seconds
DR232: 4 seconds per 300 channels (including the subunit)
(depends on the modules and number of channels)

Recording section (DR231/232 main unit)

- Recording Method
Raster scan method, 10-color wire dot recording
- Number of Recording Points
300 points maximum (stand-alone model: 30 points + AC 6 points)
- Recording Paper
Effective recording width: 250 mm (for analog trend measurement)
● Analog recording color (You can specify a color for each channel.)
Purple, red, green, blue, brown, black, navy blue, yellow-green, red-purple, orange
- Analog Recording Interval
FIX: Recording takes place at the specified measurement interval between 2 and 60 seconds (not all measured values are sampled for analog recording in case of the 0.5- and 1-second measurement intervals)
Linked to recording paper feed speed

AUTO:

- Recording Paper Feed
Paper feed speed: 1 to 1,500 mm/hour

Display Section

- Display Section
Display: VFD display (5 x 7 dot matrix, 3 lines)
Number of characters: 22 characters (large/1 line), 40 characters (2 lines)

Memory Function Section

- Memory Media
3.5-inch floppy disk drive with 512 kB SRAM buffer memory
- Data Capacity
10 data/ch to 50 kdata/ch
(Total data memory should be less than total memory length.)
- Applicable data
Setting values, measured values and computed values except report calculating values
- Memory Mode
Binary
Can be converted to ASCII (CSV) format for copying buffer memory data to floppy disk.
- Sample Rate
Synchronized with the measurement interval of the recorder unit, or synchronized with event.

Alarms

- Number of Settings
Up to four settings can be made for each channel.
- Kinds of Alarms
Upper/lower limit, difference upper/lower limit, upper/lower limit of percentage change, upper or lower limit only for the results of computation
Percentage change alarm time interval: 1 to 15 scans
- Number of Alarm Output Points
DR231: 12 maximum (alarm option: 10; DI/DO option: 2)
DR232: 300 in total

Standard Computation Functions

- Kinds of Computation
Difference between arbitrarily selected channels, linear scaling, moving average, pulse integration
Scalable range: DC voltage, thermocouple, RTD, contact
Scaling range: -30,000 to +30,000
Moving average: 2 to 64 scans
Pulse integration: Effective when a pulse input module is recognized (up to 60 channels)

Fail, Chart End Output

- (DR expandable model. The DR stand-alone model uses the /R1 option.)
Functions: Refer to the DI / DO modules.

Optional Specifications

Computation Function (M1)

- Number of Computation Channels
DR231: 30 channels maximum
DR232: 60 channels maximum
- Kinds
Remote RJC, four arithmetic operations, SQR (square root), ABS (absolute value), LOG (common or natural logarithm), EXP (exponential), statistics processing (CLOG, TLOG), logic (AND, OR, NOT, XOR), relative computation, previous data reference
CLOG: Mathematical processing within a group of data that was measured at the same time (total, maximum, minimum, average, max. - min.)
TLOG: Mathematical processing of data from a certain channel over a period of time (24 hours maximum) (total, maximum, minimum, average max. - min.)

Report Function (M3)

- Instantaneous values of measured data, as well as maximum, minimum, average and total, for each hour, day or month are printed in tabular form on recording paper. Analog recording is interrupted while a report is being made.
Report calculation channels: Up to 60 channels
Note: This function does not allow the results of the report and computing function to be saved on floppy disks. (Thus, to be able to transfer the results to a personal computer, the DP380 report software is needed. Note that the DP380 software cannot be run simultaneously with the DAQ32 or DAQ32Plus software package.)

Power Monitor Options (N7, N8)

- Applicable models and outline specifications
DR231 stand-alone model (For the DR232, the power monitor module is sold

separately.) Refer to the power monitor module.

GP-IB Communications Option (IC1)

● Applicable models and outline specifications
DR231 stand-alone model (For the DR232, the GP-IB module is sold separately.)
Refer to the GP-IB module.

RS-232C Communications Option (IC2)

● Applicable models and outline specifications
DR231 stand-alone model (For the DR232, the RS-232C module is sold separately.) Refer to the RS-232C module.

RS-422A/485 Communications Options (IC3S)

● Applicable models and outline specifications
DR231 stand-alone model (For the DR232, the RS-422A/485 modules are sold separately.) Refer to the RS-422A/485 module.

Ethernet Communications Option (IC7)

● Applicable models and outline specifications
DR231 stand-alone model (For the DR232, the Ethernet module is sold separately.) Refer to the Ethernet module.

Alarm Contact Output Option (IA4)

● Applicable models and outline specifications
DR231 stand-alone model (For the DR232, the alarm contact output module is sold separately.) Refer to the alarm output module.

Recorder Function Remote Control Option (IR1)

● Applicable models and outline specifications
DR231 stand-alone model (For the DR232, the DI/DO module is sold separately.)
The DR232 expandable model incorporates fail and chart-end outputs as standard features. Refer to the DI/DO module.

Input Module

Specifications Common to Input Module

● Normal Operating Temperature/Humidity Range
Universal, DCV/TC/DI input modules: -10 to 60°C, 20 to 80% RH (non condensing)
mA, power monitor, strain, pulse input modules: 0 to 50°C, 20 to 80% RH (non condensing)

● Withstanding Voltage
Between input terminals: 1,000 VAC (50/60 Hz) for one minute
Strain input: 50 VDC (50/60 Hz, 1 minute, except DU500-14)
Between input terminal and ground: 1,500 VAC (50/60 Hz) for one minute

Universal Input Modules

DCV/TC/DI Input Modules

Module	Model	Number of Channels	Type of Terminal	Measurement Interval
Universal input	DU100-11	10	Screw	0.5 s
	DU100-12	10	Clamp	0.5 s
	DU100-21	20	Screw	2 s
	DU100-22	20	Clamp	2 s
	DU100-31	30	Screw	2 s
	DU100-32	30	Clamp	2 s
DCV/TC/DI input	DU200-11	10	Screw	0.5 s
	DU200-12	10	Clamp	0.5 s
	DU200-21	20	Screw	2 s
	DU200-22	20	Clamp	2 s
	DU200-31	30	Screw	2 s
	DU200-32	30	Clamp	2 s

● General Specifications

Input method: Floating imbalance input, and inter-channel isolation
RTD and pulse inputs are of the same potential within the same input module.

A/D resolution: ±20,000
A/D integration time: Manual selection or automatic switchover between 20 ms (50 Hz), 16.7 ms (60 Hz) and 100 ms (10 Hz)

Measurement Range
DC voltage range: 20 mV to 50 V
Thermocouple: R, S, B, K, E, J, T, L, U, N, W, KP-Au7Fe
RTD: Pt100, JPt100, Ni100, Ni120, Cu10, and J263°B
Contact input: Voltage-free contact input or voltage input
Mixed input is allowed for DC voltage, thermocouple, RTD and contact inputs.
(For an DCV/TC/DI input module, RTD input is not allowed.)

Measurement accuracy: ±(0.05% of reading + 2 digits)
(at 2-V range, 23 ±2°C and 55 ±10% RH)

Noise rejection: By means of integrating A/D, low-pass filter or moving average

Burnout: Detected within thermocouple-input range

DC Current Input Modules

Model	Number of Channels	Type of Terminals	Measuring Interval
DU300-11	10	Screw	0.5 s
DU300-12	10	Clamp	0.5 s

● General Specifications

Input method: Floating imbalance input, and inter-channel isolation
Shunt resistor (100 Ω) is pre-installed.

A/D resolution: ±20,000
A/D integration time: Manual selection or automatic switchover between 20 ms (50 Hz), 16.7 ms (60 Hz) and 100 ms (10 Hz)

Measurement range (resolution): ±20 mA (1 μA)
Noise rejection: By means of integrating A/D, low-pass filter or moving average

Power Monitor Modules

Model	Number of Channels	Type of Terminal	Measurement Interval
DU400-12	For single phase: one for voltage and one for current	Clamp	2 s
DU400-22	For 3 phases: three for voltage and three for current	Clamp	2 s

Input method: Transformer isolation
Measured variables: Six items can be selected from the following: RMS value of AC voltage/current, active power, apparent power, reactive power, frequency, power factor and phase angle (There is a restriction in combining selected items.)

Measurement range (resolution):
Voltage: 250 V (0.1 Vrms), 25 V (0.01 Vrms)

Current: 5 A (0.001 Arms), 0.5 A (0.001 Arms)
Measurement accuracy: ±(0.5% of span when RMS V and A are measured)
Measured frequency: 45 to 65 Hz (all channels must have the same frequency)
Crest factor: Up to 3
Power integration: Calculated by /M1 (computation functions) option.
/M1 must be specified for the DR230.

Strain Measurement Modules

Model	Number of Channels	Type of Terminal	Measurement Interval
DU500-12	10*, with built-in 120 Ω resistance	Clamp	0.5 s
DU500-13	10*, with built-in 350 Ω resistance	Clamp	0.5 s
DU500-14	10*, for external bridge box	NDIS	0.5 s

*: 2 modules' width is required.

● General Specifications

Measurement range (resolution):
2,000 με (10 με), 20,000 με (1 με), 200,000 με (10 με)
Built-in bridge resistance: 120 Ω, 350 Ω, or none (for an external bridge box)
Wiring: 1/4 bridge, 1/2 bridge (neighbor), 1/2 bridge (opposite), full bridge
Applicable gaugeresistance: 1/4 or 1/2 bridge: 120 or 350 Ω
Full bridge: 100 to 1,000 Ω
Bridge voltage: Fixed at 2 V
Gauge factor: 2.00 (with scaling function)
Strain balance: Electronic auto-balancing (can be turned on or off in each module) within ±10,000 με (1/4 bridge)

Pulse Measurement Modules

Model	Number of Channels	Type of Terminal	Measurement Interval
DU600-11	10	Screw	0.5 s*

*: Rate of data update is fixed at one-second interval.

Input method: Shared common line within the same module
Type of input: Non-voltage contact or open collector (TTL or transistor)

Measurement modes

RATE (count value instantaneous mode):
The number of pulses input during the most recent one-second period of measurement is output as the scale set value.

GATE (ON time instantaneous mode):
The ON (make)/OFF (break) state (ON = 1, OFF = 0) of the contact input during the most recent one-second period of measurement is output as the scale set value.

Pulse integration: The computation function is used when integrating either the count value each second or the ON period.

Computation formula: TLOG.PSUM (XXX)

Number of computation channels: Max. 60 channels

Max. count value/ON period:
99999999
(/M1 (computation option) need not be specified for the DA100 or DR recorder main unit. Pulse integration can be used automatically when a pulse module is recognized.)

Maximum input frequency: 6 kP/s (10 P/s for voltage-free contact)
Filter: For rejection of chattering up to 5 ms (can be turned on and off for every channel)

Digital Input Module

Model	Number of Channels	Type of Terminal	Measurement Interval
DU700-11	10	Screw	0.5 s

● General Specifications

Input method: Unbalanced floating-point, with channel-to-channel isolation (individually separated channels)

Measuring range: Voltage input 2.3 V or less 0
2.5 V or greater 1
Voltage-free contact input Off (open) 0
On (closed) 1

Maximum input voltage range: Voltage input ±60 V DC
Voltage-free contact input ±10 V DC

Alarm, DI/DO and Other Modules

Alarm Contact Output Modules

Model	Number of Outputs	Contact Arrangement	Type of Terminal
DT200-11	4	SPDT (NO-C-NC)	Screw
DT200-21	10	Make contact (NO-C)	Screw

● General Specifications

Output mode: Selection between excitation and non-excitation, output hold and non-hold and AND and OR modes
Re-breakdown re-alarm: Maximum of 6 contacts can be selected.
Contact capacity: 250 VDC/0.1 A (resistive load), 30 VDC/2 A (resistive load), 250 VAC/2 A (resistive load)

DI/DO Modules

● Common Specifications

Model: DT100-11
The DR232 expandable model incorporates fail and chart-end output as standard features. (Up to 1 module can be connected to the DR230 expandable model.)

● Alarm Contact Output

Number of outputs: 2
Contact mode: C contact—NO-C-NC terminal
Contact capacity: 250 VDC/0.1 A (resistive load), 30 VDC/2 A (resistive load), 250 VAC/2 A (resistive load)

● Chart End Output

Outline of functions: The chart end output terminal is energized if the recorder paper in the recorder breaks.
The DR stand-alone model uses the /R1 option.

Contact mode: Make contact (NO-C). Cannot be switched between excited and non-excited.

Contact capacity: 250 VDC/0.1 A (resistive load), 30 VDC/2 A (resistive load), 250 VAC/2 A (resistive load)

● Fail Output

Function: If an abnormality is found in the total system, the fail output terminal is de-energized.
Output mode: Make contact (NO-C). Cannot be switched between excited and non-excited.

Contact capacity: 250 VDC/0.1 A (resistive load), 30 VDC/2 A (resistive load), 250 VAC/2 A (resistive load)

● Remote Control Signal Input

Function: Start and stop recording
Change chart speed
Start message printing
Start and stop memory sampling
Control statistical calculation interval
Non-voltage contact or open collector (TTL or transistor)

Input signal:

Extension Modules

Unit to connect with: DS400 or DS600 subunit (one for each subunit)
Number of input modules: One input module can be mounted on an extension base unit. Up to 3 extension base units can be connected to one extension module in series.

Types of input modules: 10-ch universal input module
10-ch DCV/TC/DI input module

Extensible distance: Up to total length of 30 m

Communications Modules

Specifications Common to Communications Modules

● Functions, Common Specifications

Outline of functions: Output of measured values, output of set points, setup of measurement conditions, control of start/stop of measurement, etc.

Withstanding voltage: 1,500 VAC (50/60 Hz) for one minute between output terminal and ground

GP-IB Modules

Electrical and mechanical specifications: Based on IEEE standard 488-1978
Addresses: 0 to 15

RS-232C Modules

Electrical and mechanical specifications: Based on EIA RS-232C
Communications format: Half duplex
Synchronization: Start-stop synchronization (synchronization by means of the start and stop bits)
Baud rate: 150, 300, 600, 1200, 2400, 4800, 9600, 19200 or 38400 bps
Transmission distance: Maximum of 15 m
Connector: D-sub 25-pin connector

RS-422A/485 Modules

Electrical and mechanical specifications: Based on EIA RS-422A and EIA RS-485
Connection method: Multi-point
Address: 1 to 31
Communications format: Half-duplex, 4-wire method/2-wire method
Synchronization: Start-stop synchronization (synchronization by means of start and stop bits)
Baud rate: 300, 600, 1200, 2400, 4800, 9600, 19200 or 38400 bps
Transmission distance: Maximum of 1200 m
Connector: 6-screw terminal

Ethernet Modules

Network configuration: Ethernet (10Base-T)
10Base-T modular connector: 1
Baud rate: 10 Mbps
Communication protocol: TCP, UDP, IP, ARP or ICMP
Input data: ASCII
Output data: ASCII or binary

■ Model and Suffix Codes
DR230 Stand-alone model

Model	Suffix code	Description
DR231		Desk-top type hybrid recorder
Memory	-0	No memory
	-1	3.5-inch FD
Software	0	No DAO 32 software
	2	DAO 32 software included
Input channel	-1	10 ch
	-2	20 ch
	-3	30 ch
Input	1	Universal input, screw
	2	Universal input, clamp
	3	DCV/TC/DI input screw
	4	DCV/TC/DI input clamp
Power supply voltage	-1	100 to 240 VAC
Power inlet, power cable	D	3-pin power inlet w/UL CSA cable
	F	3-pin power inlet w/VDE cable
	R	3-pin power inlet w/SAA cable
	S	3-pin power inlet w/BS cable
Additional specifications	/M1	Computing functions
	/M3	Report function
	/C1	GP-IB
	/C2	RS-232C
	/C3S	RS-422/485 (screw)
	/C7	Ethernet
	/N7	Power monitor for single phase
	/N8	Power monitor for 3 phase
	/A4	Alarm output module (A type 10 contacts)
	/R1	2-point alarm output, remote control signal input, fail output, and chart end output
	/H1	Internal illumination
	/H5	Carrying handle
/D2	°F display	
/P6	DC power supply (AC and DC power supply coexist)	

- The maximum allowable number for the / N □ / C □ / A4 and / R1 options is determined according to the specified channel number.
10 ch: All options can be specified.
20 ch: All of them can be specified.
30 ch: 3 of them can be specified.

DR230 Expandable model

Model	Suffix codes	Description
DR232		Desk-top type hybrid recorder
Memory	-0	No memory
	-1	3.5-inch FD
Data conversion	0	No DAO 32 software
	2	DAO 32 software included
Input	-00	Always -00
Power supply voltage	-1	100 to 240 VAC
Power inlet, power cable	D	3-pin power inlet w/UL CSA cable
	F	3-pin power inlet w/VDE cable
	R	3-pin power inlet w/SAA cable
	S	3-pin power inlet w/BS cable
Additional specifications	/M1	Computing function
	/M3	Report function
	/H1	Internal illumination
	/D2	°F display

- Subunits and input/output modules must be ordered separately from the main unit.
- The extension cable must be ordered separately when the subunit is specified.

Subunit: DS400, DS600

Model	Suffix codes	Description
DS400		4-module connection type subunit
DS600		6-module connection type subunit
Type	-00	Always -00
Power supply voltage	-1	100 to 240 VAC
Power inlet, power cable	D	3-pin power inlet w/UL CSA cable
	F	3-pin power inlet w/VDE cable
	R	3-pin power inlet w/SAA cable
	S	3-pin power inlet w/BS cable
	W	With 3-pin inlet screw conversion terminal

Configuration example of the expandable model

- 100 ch, 0.5 s universal input, with RS-232C and 20-ch alarm output
- DR230 expandable main-unit: DR232 × 1
- Sub unit: DS600 × 2
- Universal input module: DU100-11 or -12 × 10
- Communication module: DT300-21 (RS-232C) × 1
- Alarm output module: DT200-21 × 2
- Extension cable × 2

